Endeavor[®] 10-505, 605, 805

2-way Cabinet Indoor / Outdoor Loudspeaker

NO-805 W SOLD OUT

SPECIFICATIONS

of Een reactions	IO-505	IO-605	IO-805	
Dupont® Kevlar woofer with butyl rubber surround	5-1/4"	6-1/2"	8"	Woofer Size
Tetoron® soft dome pivoting tweeter	1"	1"	1"	Tweeter Size
Frequency Response:	40 - 21K	38 - 21K	35 - 21K	Hz
Power Handling:	50/100	60/120	70/140	watts nom. / max.
Sensitivity:	87	88	89	dB 1 watt / 1 meter
Impedance:	8	8	8	ohms
Available in White & Black Raintable Enclosures		V	Black Only	Limitod
Rust-proof Perforated Aluminum Grille which is epoxy painted for long life in high humidity and salt air environments	d 🕔		J	LIFETIME
Sold and Shipped in Pairs		V	V	Warranty
Individual Net Weight with U-Bracket	5.7	8.1	11.15	lbs

FEATURES

Sealed system design (no port) prevents bugs and moisture from entering cabinet. Indoor / outdoor bass equalization on select models.

Versatile mounting options, includes standard type "U" bracket and mounting bosses on rear for optional double-swivel mounting brackets.

Suitable for use on bookshelves with bracket-less finished look.

DIMENSIONS

RoHS

Rev. C

EDIA

IO-505: Enclosure 7-1/4" W x 10" H x 7-1/2" D mounting bracket increases depth 3/4"

IO-605: Enclosure 8-3/4" W x 11-3/8" H x 8-5/8" D mounting bracket increases depth 1"

IO-805: Enclosure 10-5/8" W x 13-3/4" H x 10-5/8" D mounting bracket increases depth 1-1/4"





notched & solid end-caps enable U-Bracket mounting or bookshelf format



DEM SYSTEMS COMPANY

(775) 355-0405 • (800) 291-0561 FAX www.oemsystems.com • info@oemsystems.com







Endeavor® 10-510

2-way Cabinet Indoor / Outdoor Loudspeaker

IO-570 70-100 Volt / 8 ohms COMMERCIAL - Indoor / Outdoor Loudspeaker

SPECIFICATIONS

	IO-510	IO-570	
Polypropylene woofer with butyl rubber surround	5-1/4"	5-1/4"	Woofer Size
Mylar soft dome pivoting tweeter	1"	1"	Tweeter Size
Frequency Response:	42 - 21K	42 - 21K	Hz
Power Handling:	50 / 100	50 / 100	watts nom. / max.
Sensitivity:	90	90	dB 1 watt / 1 meter
Impedance:	8	8*	ohms
Available in White & Black Paintable Enclosures			Limitod
Rust-proof Perforated Aluminum Grille which is epoxy painted for long life in high humidity and salt air environments		J	LIFETIME
Sold and Shipped in Pairs			Warranty
Individual Net Weight with U-Bracket	5.25	6.6	lbs
	1		

* In 8-ohm position

FEATURES

Sealed system design (no port) prevents bugs and moisture from entering cabinet.

Versatile mounting options, includes standard type "U" bracket and mounting bosses on rear for optional double-swivel mounting brackets

DIMENSIONS

IO-510: Enclosure 7-1/4" W x 10" H x 7-1/2" D mounting bracket increases depth 3/4" IO-570: Enclosure 7-1/4" W x 10" H x 7-1/2" D mounting bracket increases depth 3/4"



CEDIA

RoHS





Front mounted 70-100 Volt tap selector switch with bypass setting for 8-ohm applications **Tap Selection Settings:** 2, 4, 8, 16, 32W (70V) & 4, 8, 16, 32W (100V)





(775) 355-0405 • (800) 291-0561 FAX www.oemsystems.com • info@oemsystems.com

Rev. B

Rev. B

Silicon-Encapsulated, High-Grade Crossovers **IR Knockouts**

DIMENSIONS & WEIGHTS

Cut-out: 7-3/8" W x 10-7/8" H x 3-1/4" D Overall: 8-5/8" W x 12-1/8" H x 3-1/4" D

Shipping Weight: 12 lbs pair Net Weight: 5.25 lbs pair

RoHS

CEDIA

» 30-60 Watts

CHE OU

Rust Proof Grilles are aluminum, epoxy-painted for long life in high humidity and salt air environments

Clamp Ring Mounting System

» 8 Ohms

» Anti corrosive materials throughout » Rubber Gaskets & Hardware Seals

FEATURES

» 45 Hz - 21,000 Hz

LOUPSPEAKER

AW-700

Built to weather the elements

SPECIFICATIONS

» Stainless Steel Hardware

1/2" 2-way Loudspeaker

» 6-1/2" Carbon Fiber impregnated Polycone Woofer w/ Butyl Rubber Surround » 1" Weatherized Titanium Dome Tweeter » Gold Plated High-TensionTerminals » Epoxy-Painted Aluminum Grille





