



SC-502E

5-1/4" In-Ceiling Loudspeaker

5-1/4" 2-way Loudspeaker

Frequency Response: 50Hz - 20kHz ± 3 dB

Power Handling: 30 watts nom. 60 max.

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: 3/4" pivoting, dome tweeter

Cut-out dimensions: 6-1/2" dia. x 2-3/8" deep

Overall dimensions: 7-1/2" dia.

Sold and shipped in pairs

Features:

- Polypropylene woofer with butyl rubber surround
- Proven dog ear mounting system
- Frame and Grilles may be painted to match mounting surface



Optional Pre-Construction Brackets & Vapor Domes

SC-602E

6-1/2" In-Ceiling Loudspeaker

6-1/2" 2-way Loudspeaker

Frequency Response: 45Hz - 20kHz ± 3 dB

Power Handling: 40 watts nom. 80 max.

Sensitivity: 91dB 1 watt / 1 meter

Impedance: 8 ohms nominal

Tweeter: 3/4" pivoting, dome tweeter

Cut-out dimensions: 7-3/8" dia. x 2-7/8" deep

Overall dimensions: 8-3/8" dia.

Sold and shipped in BULK 4-packs (2 pairs)

Supplied with grille, baffle & frame

