

Presence®

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



PV-6LCRS

6-1/2" In-Ceiling 2-way
15° Angled Loudspeaker

PV-8LCRS

8" In-Ceiling 2-way
15° Angled Loudspeaker

PV-LCRS

Dual 5-1/4" In-Wall 2-way
Center / All Channel Loudspeaker

	PV-6LCRS	PV-8LCRS	PV-LCRS	
Poly Woofer with Butyl Rubber Surround	6-1/2"	8"	Dual 5-1/4"	Woofer Size
Silk, Soft-Dome, Pivoting Tweeter	3/4"	3/4"	1"	
Frequency Response	50 - 20K	35 - 20K	45 - 20K	Hz ± 3 dB
Power Handling	40 / 80	60 / 120	50 / 100	watts nom. / max.
Sensitivity	91	91	91	dB 1 watt / 1 meter
Impedance	8	8	8	ohms
Overall Dimensions	7-1/2" Diameter	12-7/8" Diameter	9" x 15-3/4"	
Cut-Out Dimensions	6-1/2" Diameter	11-1/2" Diameter	7-7/8" x 14-7/16"	
Loudspeaker Depth	2-3/8"	5-3/4"	3-1/2"	

Features:

- High-temperature Polyimide voice coils
- High-grade crossovers
- Polyswitch overdrive protection
- Proven mounting system
- Frame and Grille may be painted to match mounting surface
- Sold and Shipped Individually

Optional Pre-Construction Brackets



Additional PV-LCRS Features:

- Phase plug pole piece extensions | IR Knockouts | Magnetically Shielded | Orient Vertically or Horizontally | Industry Leading Superior Clamp-ring Mounting System



Supplied with grille, baffle & frame

Welcome Home



OEM SYSTEMS COMPANY
(775) 355-0405 ♦ (800) 291-0561 FAX
www.oemsystems.com ♦ info@oemsystems.com

View all our
Presence
Models:

