

Premium Series

Rigid captive clamp-ring mounting system
Fine mesh grilles
Lifetime Limited Warranty



SE-691E

5 ¼" long throw poly woofer with butyl surround
1" pivoting soft textile dome tweeter
91 dB sensitivity
Frequency Response: 50 Hz - 20,000Hz
Power Handling: 30 watts nom. 60 watts max.
8 Ohms
Cut-out dimensions: 5 9/16" W x 8 1/4" H x 2 3/8" D
Overall dimensions: 6 5/8" W x 9 1/4" H



SE-791E

6 ½" long throw poly woofer with butyl surround
1" pivoting soft textile dome tweeter
Poly-switch overdrive protection
IR knock-out
91 dB sensitivity
12 dB/Octave crossover
Frequency Response: 45 Hz - 20,000 Hz
Power Handling: 40 watts nom. 80 watts max.
8 Ohms
Cut-out dimensions: 7 3/8" W x 10 7/8" H x 3 1/8" D
Overall dimensions: 8 5/8" W x 12 1/8" H

SE-791DE
model
available
with
dog ear
mounting
system



SE-891E

8" long throw poly woofer with butyl surround
1" pivoting soft textile dome tweeter
Poly-switch overdrive protection
IR knock-out
91 dB sensitivity
12 dB/Octave crossover
Frequency Response: 35 Hz - 20,000 Hz
Power Handling: 50 watts nom. 100 watts max.
8 Ohms
Cut-out dimensions: 9" W x 13" H x 2 15/16" D
Overall dimensions: 10 1/2" W x 14 1/2" H


ArchiTECH

In-Wall Loudspeaker Products®



Premium Series

Fine mesh grilles
Lifetime Limited Warranty



SC-502E

5 1/4" poly woofer with butyl surround
3/4" pivoting dome tweeter
91 dB sensitivity
Frequency Response: 50 Hz - 20,000Hz
Power Handling: 30 watts nom. 60 watts max.
8 Ohms
Cut-out dimensions: 6 1/2" round x 2 3/8" deep
Overall dimensions: 7 1/2" round



SC-602E

6 1/2" poly woofer with butyl surround
3/4" pivoting dome tweeter
91 dB sensitivity
Frequency Response: 45 Hz - 20,000 Hz
Power Handling: 40 watts nom. 80 watts max.
8 Ohms
Cut-out dimensions: 7 3/8" round x 2 7/8" deep
Overall dimensions: 8 3/8" round



SC-802E

8" poly woofer with butyl surround
3/4" pivoting dome tweeter
91 dB sensitivity
12 dB/Octave crossover
Frequency Response: 35 Hz - 20,000 Hz
Power Handling: 50 watts nom. 100 watts max.
8 Ohms
Cut-out dimensions: 8 5/8" round x 2 7/8" deep
Overall dimensions: 9 3/4" round

OEM Systems Company, Inc.

740 Freeport Boulevard, #106, Sparks, NV 89431-6168 Phone: (775) 355-0405 Fax: (800) 291-0561

www.oemsystems.com info@oemsystems.com