



AP-611 6 1/2" 2-Way Single Point Stereo In-Ceiling Loudspeaker

Long throw Poly woofers with Butyl rubber surrounds
Dual (left & right) 3/4" Mylar ferro-fluid cooled dome tweeters

- 6 1/2" 2-Way round Single Point Stereo
- Frequency response: 45 Hz – 20 kHz ± 4 dB
- Power handling: 50 watts nom. 100 max both
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 8 3/8" round
- Cut-out: 7 3/8" round x 2 7/8" deep
- Pre-construction bracket: RIR-6
- Pre-construction bracket with Vapor Dome: VPD-6
- Stainless-steel grilles and screws for high humidity environments



AP-601 6 1/2" 2-Way Round In-Ceiling Loudspeakers

Long throw Poly woofers with Butyl rubber surrounds
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters

- 6 1/2" 2-Way round
- Frequency response: 45 Hz – 20 kHz ± 4 dB
- Power handling: 50 watts nom. 100 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 8 3/8" round
- Cut-out: 7 3/8" round x 2 7/8" deep
- Pre-construction bracket: RIR-6
- Pre-construction bracket with Vapor Dome: VPD-6



AP-801 8" 2-Way Round In-Ceiling Loudspeakers

Long throw Poly woofers with Butyl rubber surrounds
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters

- 8" 2-Way round
- Frequency response: 40 Hz – 20 kHz ± 4 dB
- Power handling: 60 watts nom. 120 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 9 3/4" round
- Cut-out: 8 5/8" round x 3 3/8" deep
- Pre-construction bracket: RIR-8
- Pre-construction bracket with Vapor Dome: VPD-8



AP-615 LCERS 6 1/2" 2-Way Round In-Ceiling All Channel Loudspeaker

Long throw Poly woofers with Butyl rubber surround
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters

- 6 1/2" 2-Way round 15° Angled
- Frequency response: 45 Hz – 20 kHz ± 4 dB
- Power handling: 50 watts nom. 100 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Anti-Diffraction foam covered baffle surface
- Overall dimension: 10 3/4" round
- Cut-out: 9 1/4" round x 5" deep
- Pre-construction bracket: RIR-615



AP-815 LCERS 8" 2-Way Round In-Ceiling All Channel Loudspeaker

Long throw Poly woofers with Butyl rubber surround
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters

- 8" 2-Way round 15° Angled
- Frequency response: 40 Hz – 20 kHz ± 4 dB
- Power handling: 60 watts nom. 120 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Anti-Diffraction foam covered baffle surface
- Overall dimension: 12 7/8" round
- Cut-out: 11 1/2" round x 5 3/4" deep
- Pre-construction bracket: RIR-815



AP-602 6 1/2" 2-Way Rectangular In-Wall Loudspeakers

Long throw Poly woofers with Butyl rubber surrounds
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters
Mounting provision for IR device

- 6 1/2" 2-Way Rectangular
- Frequency response: 45 Hz – 20 kHz ± 4 dB
- Power handling: 50 watts nom. 100 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 9 1/16"W x 12 3/4"H
- Cut-out: 8"W x 11 1/4"H x 3 1/4" deep
- Pre-construction bracket: RIB-62



AP-802 8" 2-Way Rectangular In-Wall Loudspeakers

Long throw Poly woofers with Butyl rubber surrounds
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters
Mounting provision for IR device

- 8" 2-Way Rectangular
- Frequency response: 40 Hz – 20 kHz ± 4 dB
- Power handling: 60 watts nom. 120 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 10 1/2"W x 14 1/2"H
- Cut-out: 9"W x 13"H x 3 1/4" deep
- Pre-construction bracket: RIB-82
- Pre-construction bracket with Vapor Dome: VPD-82



AP-525 LCERS Dual 5 1/4" 2-Way All Channel In-Wall Loudspeaker

Long throw Poly woofers with Butyl rubber surround
Pivoting 1" Mylar soft dome ferro-fluid cooled tweeters
Mounting provision for IR device

- Dual 5 1/4" 2-Way Rectangular MTM
- Frequency response: 45 Hz – 20 kHz ± 4 dB
- Power handling: 50 watts nom. 100 max.
- Sensitivity: 91dB 1 watt / 1 meter
- Impedance: 8 ohm nominal
- Overall dimension: 9"W x 15 3/4"H
- Cut-out: 7 7/8" x 14 7/16" x 3 1/2" deep
- Pre-construction bracket: RIB-LCR
- Orient vertically or horizontally

