

Presence[®]

LOUDSPEAKERS FOR TODAY'S ARCHITECTURE



A-525CC Dual 5-1/4" 2-way MTM LCRS Loudspeaker

The A-525CC has been optimized for high fidelity home theatre applications, primarily as a center channel speaker. The broad dispersion design does not limit the sweet spot to just one seat in the room but provides a large sound field to enjoy hi-fi audio.



Frequency Response: 80Hz - 20kHz \pm 3 dB

Power Handling: 60 watts nom. 120 max.

Sensitivity: 89dB 2.83V / 1 meter

Impedance: 8 ohms nominal, 6 ohms minimum

Tweeter: 1" Silk dome ferro-fluid cooled tweeter with acoustically optimized aluminum baffle

Overall Dimensions: 18-5/16"W x 6-11/16"H x 6-5/8"D (including grille)

Sold and shipped individually

Features:

- Dual 5-1/4" Magnetically shielded Kevlar[®] Woofers with butyl rubber surrounds
- Non-reflective-black MDF cabinet
- Equally suitable for left/right primary and surround channels
- Gold-Plated spring-post connections that accept up to #10 wire & dual banana plugs
- Proven mounting system

Rear Gold-Plated
Spring-Post
Connections



Supplied with Black Cloth Grille



Welcome Home



OEM SYSTEMS COMPANY
(775) 355-0405 ♦ (800) 291-0561 FAX
www.oemsystems.com ♦ info@oemsystems.com

View all our
Presence
Models:



Rev. E