



The SLX-4 can be used as a distribution point when multiple speakers are connected to an amplifier. This can reduce wiring clutter and offer a cleaner and more reliable installation. It is also useful for isolating areas of distributed sound. This can permit private listening and prevent disruption to offices or guest and children's rooms. Beyond these benefits, the SLX-4 can also help to protect the amplifier from damage by reducing or balancing the load.

Features

Positive connections that will not work themselves loose like the popular "spring clip" or "quick connect" types

Dramatic time savings in installation and set-up

Dramatic improvement in connection integrity - absolutely superior quality terminations

Makes troubleshooting system connections extremely quick and easy

Individual on/off switches for each pair of speakers

Provided with 120 high quality pre-printed speaker selector labels

MB-4 wiring harness connection system included

EXT-6 wiring harness connection system - 6' extension - optional

A/B Source Switching

125 watts / channel power handling

Sold and Shipped Individually

Dimensions

Width: 8-1/2"

Height: 2-5/8" x 9" Depth

Shipping Weight: 6 lbs



MB-4



Each MB-4 provides connections for 4 pairs of speakers. The MB-4 wiring harness is approximately 4' in length. It is terminated on one end with a 16 conductor molded nylon locking connector and 16 high-grade gold plated banana plugs on the other end. The nylon connector snaps and locks into the rear panel of the SLX-4. These connections are not subject to "working loose" or becoming loose from minor movement.